



■ MOTOR CONNECTIONS



■ Encoder pin definitions



PIN NO.#	DESCRIPTION	COLOR(颜色)	DESCRIPTION	COMMON RATINGS
PN1	GND	BLACK(黑色)	POWER 0V DC	1.8°
PN2	VCC	RED(红色)	POWER 5V DC	POSITION ACCURACY 1.8° ± 0.09°
PN3	PA+	YELLOW(黄)	ENCODER A PLUS	2
PN4	PA-	GREEN(绿)	ENCODER A MINUS	80° C
PN5	PB+	BLUE(蓝)	ENCODER B PLUS	500VDC
PN6	PB-	WHITE(白)	ENCODER B MINUS	100MΩHM(50VDC)
DC RESISTANCE: Ω ± 10%				MAXO.025MM(LOAD450G)
INDUCTANCE /PHASE: mH ± 20%				MAXO.075MM(LOAD920G)
HOLDING TORQUE: N.M				
INERTIA: KG.CM2				
WEIGHT: KGS				

DESCRIPTION	COMMON RATINGS	比例	日期	产型	品号	公司名	公司网址
POWER 0V DC	1.8°	1:1		86J1181566C-1000-LS-14-HBL		深圳市杰美康机电有限公司	www.jmc-motion.com
POWER 5V DC	POSITION ACCURACY 1.8° ± 0.09°					Shenzhen Just Motion Control	
ENCODER A PLUS	2					Electromechanics Co., LTD	
ENCODER A MINUS	80° C						
ENCODER B PLUS	500VDC						
ENCODER B MINUS	100MΩHM(50VDC)						
ENCODER B MINUS	MAXO.025MM(LOAD450G)						
ENCODER B MINUS	MAXO.075MM(LOAD920G)						

