



MOTOR CONNECTIONS



Encoder pin definitions



SPECIFICATION	
CURRENT / PHASE: A	5
DC RESISTANCE: $\Omega \pm 10\%$	0.45
INDUCTANCE / PHASE: mH $\pm 20\%$	1.8
HOLDING TORQUE: N.M	3.0
INERTIA: G.CM2	690
WEIGHT: KGS	1.4

PN NO#	DESCRIPTION	COLOR(颜色)	DESCRIPTION	COMMON RATINGS
PN1	GND	BLACK(黑色)	POWER OV DG	1.8°
PN2	VCC	RED(红色)	POWER 5V DG	1.8° $\pm 0.09^\circ$
PN3	PA+	YELLOW(黄)	ENCODER A PLUS	2
PN4	PA-	GREEN(绿)	ENCODER A MINUS	80° C
PN5	PB+	BLUE(蓝)	ENCODER B PLUS	500VDC
PN6	PB-	WHITE(白)	ENCODER B MINUS	1000MOM(500VDC)
PN7	SHIELDED	SHIELDED(屏蔽)	SHIELDED	MAXX.025MM(0.01450)
PN8	NC	NC	NC	MAXX.075MM(LOAD9200)
PN9	NC	NC	NC	B

比例	1:1	日期		产品名称	6011887EC-1000-1S
视图方向	60度相视	绘图		产品系列	混合步进伺服
审核		公司	名称	公司名称	深圳市杰美康机电有限公司
		网址		公司网址	Shenzhen Just Motion Control Electromechanics Co., LTD www.jmc-motion.com

